

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922) 49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Ижевск (3412)26-03-58
Иваново (4932)77-34-06
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Россия (495)268-04-70

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Саранск (8342)22-96-24
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сыктывкар (8212)25-95-17
Сургут (3462)77-98-35
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Казахстан (772)734-952-31

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://exotek.nt-rt.ru> || exox@nt-rt.ru

Влагомер древесных опилок MC-600SD

APPLICATIONS & FEATURES

Sawdust Moisture Meter MC-600SD-A is a state-of-the-art device for measuring moisture contents in sawdust, wood shavings, slivers and other finely crumbled wood waste. The instrument can also Measure Moisture in Straw any Hay. Excellent to use when producing Biofuel Products such as Pellets (Pelletizing) or making Briquettes.

The Moisture Meter measures the resistance of a compressed sample of sawdust or straw.

The measurement is made in two stages:

1. The sample is compressed to the pressure of approx. 0.2 MPa.
2. The resistance of the sample is measured and converted into moisture contents.

Features:

- Fast read out of Moisture content in Sawdust and Hay.

TECHNICAL SPECIFICATION	MC-600SD
MATERIALS	Sawdust
MEASURING PRINCIPLE	Resistance type
MEASURING RANGE SAWDUST	MC-600SD-A: 8- 50 % H ₂ O
MEASURING RANGE HAY, STRAW	MC-600SD-A: 10- 30 % H ₂ O Relative Moisture Content
ACCURACY	Range (of measured value.) 8-15 % ± 1 % 16-28 % ± 2 %
COMPRESSIONS PRESSURE	0.2 MPa
SAMPEL VOLUME	120 cm ³
AUTOMATIC SHUT DOWN	After 15 Minutes
BATTERY WARNING	Yes
DISPLAY	LCD 3 ½ digits
RESOLUTION	Wood 1 %
Ambient temperature:	0 - +50°C
Ambient Relative humidity:	0 – 85 %RH
BATTERIES	9 V
SIZE (L x H x D)	300 x 215 x 65 mm
WEIGHT (INCL. BATTERY)	1 kg
WARRANTY	1 Year



The MC-600SD is delivered with Hard case battery English and Swedish Manual ready to use.